


Mesquite

Modules

Preliminary Technical Information Sheet

N-type Bifacial TOPCon Technology



695 W ~ 725 W

MQ7N-695 | 700 | 705 | 710 | 715 | 720 | 725TB-AG

MORE POWER



Module power up to 725 W
Module efficiency up to 23.3 %



Up to 85% Power Bifaciality,
more power from the back side



Excellent anti-LeTID & anti-PID performance.
Low power degradation, high energy yield



Lower temperature coefficient (Pmax): -0.29%/°C,
increases energy yield in hot climate



Lower LCOE & system cost



**Enhanced Product Warranty on Materials
and Workmanship***



Linear Power Performance Warranty*

1st year power degradation no more than 1%

Subsequent annual power degradation no more than 0.4%

*According to the applicable Mesquite Limited Warranty Statement.

MORE RELIABLE



Tested up to ice ball of 35 mm diameter
according to IEC 61215 standard



Minimizes micro-crack impacts



Heavy snow load up to 5400 Pa,
wind load up to 2400 Pa

MANAGEMENT SYSTEM CERTIFICATES


ISO 9001: 2015 / Quality management system
ISO 14001: 2015 / Standards for environmental management system
ISO 45001: 2018 / International standards for occupational health & safety
IEC 62941: 2019 / Photovoltaic module manufacturing quality system

PRODUCT CERTIFICATES


Coming soon.

ENGINEERING DRAWING (mm)


Rear View



Frame Cross Section A-A



MQ7N-695TB-AG / I-V CURVES



ELECTRICAL DATA | STC*

		Nominal Max. Power (Pmax)	Opt. Operating Voltage (Vmp)	Opt. Operating Current (Imp)	Open Circuit Voltage (Voc)	Short Circuit Current (Isc)	Module Efficiency
MQ7N-695TB-AG		695 W	39.8 V	17.47 A	47.7 V	18.44 A	22.4%
	Bifacial Gain**						
	5%	730 W	39.8 V	18.34 A	47.7 V	19.36 A	23.5%
	10%	765 W	39.8 V	19.22 A	47.7 V	20.28 A	24.6%
MQ7N-700TB-AG		700 W	40.0 V	17.51 A	47.9 V	18.49 A	22.5%
	Bifacial Gain**						
	5%	735 W	40.0 V	18.39 A	47.9 V	19.41 A	23.7%
	10%	770 W	40.0 V	19.26 A	47.9 V	20.34 A	24.8%
MQ7N-705TB-AG		705 W	40.2 V	17.55 A	48.1 V	18.54 A	22.7%
	Bifacial Gain**						
	5%	740 W	40.2 V	18.43 A	48.1 V	19.47 A	23.8%
	10%	776 W	40.2 V	19.31 A	48.1 V	20.39 A	25.0%
MQ7N-710TB-AG		710 W	40.4 V	17.59 A	48.3 V	18.59 A	22.9%
	Bifacial Gain**						
	5%	746 W	40.4 V	18.47 A	48.3 V	19.52 A	24.0%
	10%	781 W	40.4 V	19.35 A	48.3 V	20.45 A	25.1%
MQ7N-715TB-AG		715 W	40.6 V	17.63 A	48.5 V	18.64 A	23.0%
	Bifacial Gain**						
	5%	751 W	40.6 V	18.51 A	48.5 V	19.57 A	24.2%
	10%	787 W	40.6 V	19.39 A	48.5 V	20.50 A	25.3%
MQ7N-720TB-AG		720 W	40.8 V	17.67 A	48.7 V	18.69 A	23.2%
	Bifacial Gain**						
	5%	756 W	40.8 V	18.55 A	48.7 V	19.62 A	24.3%
	10%	792 W	40.8 V	19.44 A	48.7 V	20.56 A	25.5%
MQ7N-725TB-AG		725 W	41.0 V	17.71 A	48.9 V	18.74 A	23.3%
	Bifacial Gain**						
	5%	761 W	41.0 V	18.60 A	48.9 V	19.68 A	24.5%
	10%	798 W	41.0 V	19.48 A	48.9 V	20.61 A	25.7%
MQ7N-725TB-AG		725 W	41.0 V	17.71 A	48.9 V	18.74 A	23.3%
	Bifacial Gain**						
	20%	864 W	40.8 V	21.20 A	48.7 V	22.43 A	27.8%
	20%	870 W	41.0 V	21.25 A	48.9 V	22.49 A	28.0%

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.
** Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

ELECTRICAL DATA

Operating Temperature	-40°C ~ +85°C
Max. System Voltage	1500 V (IEC/UL) or 1000V (IEC/UL)
Module Fire Performance	TYPE 29 (UL 61730) or CLASS C (IEC61730)
Max. Series Fuse Rating	35 A
Protection Class	Class II
Power Tolerance	0 ~ + 10 W
Power Bifaciality*	80 %

* Power Bifaciality = $P_{max_{rear}} / P_{max_{front}}$, both $P_{max_{rear}}$ and $P_{max_{front}}$ are tested under STC, Bifaciality Tolerance: $\pm 5 \%$

* The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Mesquite reserves the right to make necessary adjustment to the information described herein at any time without further notice.
Please be kindly advised that PV modules should be handled and installed by qualified people who have professional skills and please carefully read the safety and installation instructions before using our PV modules.

ELECTRICAL DATA | NMOT*

	Nominal Max. Power (Pmax)	Opt. Operating Voltage (Vmp)	Opt. Operating Current (Imp)	Open Circuit Voltage (Voc)	Short Circuit Current (Isc)
MQ7N-695TB-AG	526 W	37.6 V	13.97 A	45.2 V	14.87 A
MQ7N-700TB-AG	529 W	37.8 V	14.00 A	45.4 V	14.91 A
MQ7N-705TB-AG	533 W	38.0 V	14.03 A	45.5 V	14.95 A
MQ7N-710TB-AG	537 W	38.2 V	14.06 A	45.7 V	14.99 A
MQ7N-715TB-AG	541 W	38.4 V	14.09 A	45.9 V	15.03 A
MQ7N-720TB-AG	544 W	38.6 V	14.12 A	46.1 V	15.07 A
MQ7N-725TB-AG	548 W	38.8 V	14.15 A	46.3 V	15.11 A

* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m² spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

MECHANICAL DATA

Specification	Data
Cell Type	TOPCon cells
Cell Arrangement	132 [2 x (11 x 6)]
Dimensions	2384 x 1303 x 35 mm (93.9 x 51.3 x 1.38 in)
Weight	37.9 kg (83.6 lbs)
Front Glass	2.0 mm heat strengthened glass with anti-reflective coating
Back Glass	2.0 mm heat strengthened glass
Frame	Anodized aluminium alloy
J-Box	IP68, 3 bypass diodes
Cable	6.0 mm² (IEC), 10 AWG (UL)
Cable Length (Including Connector)	360 mm (14.2 in) (+) / 200 mm (7.9 in) (-) or customized length*
Connector	T6 or MC4-EVO2 or MC4-EVO2A
Per Pallet	31 pieces
Per Container (40' HQ)	558 pieces or 496 pieces (only for US & Canada)

* For detailed information, please contact your local Mesquite sales and technical representatives.

TEMPERATURE CHARACTERISTICS

Specification	Data
Temperature Coefficient (Pmax)	-0.29 % / °C
Temperature Coefficient (Voc)	-0.25 % / °C
Temperature Coefficient (Isc)	0.05 % / °C
Nominal Module Operating Temperature	41 ± 3°C

PARTNER SECTION

